


Überblick

Informationen zum Produkt



DS2.5-3L-PE-11040000129

Multi-level terminal block, connector method: Push-in connector, Number of connectors: 6, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 26 - 12, Width: 5.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

Produktvorteile

- ☑ Multi-level terminal block.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Unique plug-in bridge, high circuit connection efficiency.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Overview

Connection method	Push in connection
Number of rows	3
number of connections	6
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

End plate width	2.2mm
width	5.2mm

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	6KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Zubehör

Marker

Top marker	/
Side marker	ZSF5
Marker support	DMTH5-2 / DMTH5-3

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-5.2
End cover	D-DS2.5-3L

Installation

End clamp	E-WS N / E-PC-1100A
-----------	---------------------

Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Die Geschäftsdaten

Nummer der Bestellung	11040000129
Verpackung Einheit	50
Minimale Bestellmenge	50
Produktgewicht (ohne Verpackung)	24.63