

Überblick

Informationen zum Produkt

**ESS-120A-25-C-BK-00-20160003056**

Energy Storage Connector, Product range: ESS socket, Color: black, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Crimp, Contact type: Needle

Produktvorteile

- ☒ Exclusive patents
- ☒ IP67 protection
- ☒ With safety locking latch
- ☒ The plug can rotate 360° after assembled
- ☒ The socket is with hand-proof protection
- ☒ With color-coded and mechanism-coded design avoiding misplug

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell



Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
Insertion force	<60N

Pullout force	>10N
---------------	------

Electrical parameters

Rated current	120A
	UL DC1500V
Insulation resistance	>5000MΩ

Electrical parameters

Pollution level	3
Contact resistance	≤0.5mΩ

Wiring data

Wiring mode	Crimp
-------------	-------

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	20160003056
-----------------------	-------------

Verpackung Einheit	32
Minimale Bestellmenge	50
Produktgewicht (ohne Verpackung)	26.2