

Überblick

Informationen zum Produkt



ESP-120A-25-OR-00-20160000014

Energy storage connector, Product range: ESP plug, color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: crimped, Contact type: hole type, min. Cable diameter: 9 mm, Max. Cable diameter: 10.5 mm

Produktvorteile

- ☒ Exclusive patents
- ☒ IP67 protection
- ☒ With safety locking latch
- ☒ The plug can rotate 360° after assembled
- ☒ The socket is with hand-proof protection
- ☒ With color-coded and mechanism-coded design avoiding misplug

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
----------------	-----

Insertion force	<60N
Pullout force	>10N

Electrical parameters

Rated current	120A
	UL DC1500V
Insulation resistance	>5000MΩ

Electrical parameters

Pollution level	3
Contact resistance	≤0.5mΩ

Wiring data

Cable sectional area	4AWG(25mm²)
Number of connections	1
Cable outer diameter	9~10.5mm
Cable stripping length	13~14mm
Wiring mode	Crimp

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Clamping ring material	Silicone
O-ring material	Silicone
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Contact material	Copper alloy

Shell color	Orange
Flammability rating	UL94V-0

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	20160000014
Verpackung Einheit	30
Minimale Bestellmenge	50
Produktgewicht (ohne Verpackung)	38