

## Überblick

### Informationen zum Produkt



## WSF4-TA-08A(H)-11030000564

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 24 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup>- 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 6 mm, Fuse type: Glass / ceramics / ..., Fuse type: G / 5 x 20, Color: black, Suitable for 24 V DC LED, Mounting type: NS 35/7.5, NS 35/15.

### Produktvorteile

- ☒ WS Fuse wire terminal;
- ☒ spring-cage connection technology, good anti-vibration performance;
- ☒ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☒ Unique plug-in bridge, high circuit connection efficiency;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

### Zertifizierung von Produkten



## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 2                      |
| Open-end side panels                      | no                     |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |
| fuse                                      | G/5 x 20               |

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Fuse type                             | Glass/ceramic/...                             |
| Dimension                             |                                               |
| NS 35/7,5 Height                      | 68mm                                          |
| NS 35/15 Height                       | 75.5mm                                        |
| length                                | 60mm                                          |
| width                                 | 6mm                                           |
| Height                                | 66.6mm                                        |
| Wiring data                           |                                               |
| Strip length                          | 10~12mm                                       |
| Conductor cross section solid         | 0.2~4mm <sup>2</sup>                          |
| Conductor cross section flexible      | 0.2~4mm <sup>2</sup>                          |
| Conductor cross section solid AWG     | 28~12                                         |
| Environmental conditions              |                                               |
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |
| IEC Electrical parameters             |                                               |
| Rated current (III / 3)               | 6.3A                                          |
| Environmental protection              |                                               |
| REACH SVHC                            | Lead 7439-92-1                                |
| RoHS                                  | No excessive harmful substances               |

## Zubehör

### Marker

|             |     |
|-------------|-----|
| Top marker  | ZB6 |
| Side marker | /   |

|                |      |
|----------------|------|
| Marker support | /    |
| Warning cover  | EEA4 |

#### Accessories

|                                                    |         |
|----------------------------------------------------|---------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P)                               | WFA4    |
| Alternate jumper (2P)                              | WFB4    |
| Staggered jumper (2P)                              | /       |
| End cover                                          | /       |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Die Geschäftsdaten

|                                  |             |
|----------------------------------|-------------|
| Nummer der Bestellung            | 11030000564 |
| Verpackung Einheit               | 115         |
| Minimale Bestellmenge            | 115         |
| Produktgewicht (ohne Verpackung) | 13.69       |