


Überblick

Informationen zum Produkt



15EDGVMG-3.5-10030009828

Pluggable terminal blocks, Rated current: 7A. Rated voltage
(II / 2) : 250V, pitch: 3.5mm, Color: green, Contact surface : Tin

Produktvorteile

- ☒ PCB welding base
- ☒ Flexible supporting a variety of plugs

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Packaging information

Type of packaging

bag packaging

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	7A

Rated current(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	green
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	15EDG-PWP
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten	
Nummer der Bestellung	10030009828
Verpackung Einheit	2400
Minimale Bestellmenge	2400
Produktgewicht (ohne Verpackung)	0.59375