

Überblick

Informationen zum Produkt



2EDGKNH-5.08-10020006693

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(III/2) : 400V, pitch: 5.08mm, Color: black, Contact surface : Tin

Produktvorteile

- ☒ Double-layer compact design
- ☒ PUSH-IN connection technology, fast wiring

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Packaging information

Type of packaging

bag packaging

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~1.5mm²

AWG

24~16AWG

Strip length

10mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated current(III/3)	250V
Rated current	8A
Rated current(III/2)	400V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection method	Push-in spring connection
Pitch	5.08mm
Number of potentials	6
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black

Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Zubehör

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten	
Nummer der Bestellung	10020006693
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	