

Überblick

Informationen zum Produkt



9EDGKD-7.62-10020007234

Pluggable terminal blocks, Rated current: 20A, Rated voltage
(III/2) : 630V, pitch: 7.62mm, Color: black, Contact surface : Tin

Produktvorteile

- ☑ Compact design, save space in the cabinet
- ☑ PUSH-IN connection technology, fast wiring
- ☑ Safety buckle design, stable connection

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Packaging information

Type of packaging

bag packaging

Connection capacity

Conductor cross section solid

0.5~4mm²

Conductor cross section flexible

0.5~2.5mm²

AWG

20~2AWG

Strip length

10mm

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated current (B)	20A
Rated current (C)	20A

Electrical parameters IEC

Rated voltage	630V
Rated current(III/3)	400V
Rated current	20A
Rated current(III/2)	630V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection method	Push-in spring connection
Pitch	7.62mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	400V
Glow Wire Flammability Index GWFI	850

Shell color	Black
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~120°C
---------------------------------	-------------

Zubehör

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten

Nummer der Bestellung	10020007234
Verpackung Einheit	
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	