

Überblick

Informationen zum Produkt



9EDGKG-5.08-10020007123

Pluggable terminal blocks, Rated current: 16A. Rated voltage
(III/2) : 160V, pitch: 5.08mm, Color: black, Contact surface : Tin

Produktvorteile

- ☒ Suitable for a variety of sockets
- ☒ PUSH-IN connection technology, quick wiring
- ☒ Both sides with operating rods, easy to pull out

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Packaging information

Type of packaging

bag packaging

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~2.5mm²

AWG

28~14AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	14.5A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	160V
Rated current(III/3)	160V
Rated current	16A
Rated current(III/2)	160V
Rated current(II/2)	320V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection method	spring-cage connection
Pitch	5.08mm
Number of potentials	5
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	Gold plate
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850

Shell color	Black
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Zubehör

Tool	
Screwdriver	/
Operating tool	DG010
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten

Nummer der Bestellung	10020007123
Verpackung Einheit	840
Minimale Bestellmenge	840
Produktgewicht (ohne Verpackung)	10.35